

**Step 1:** Remove plastic trim on top of chrome bumper. This is done by removing a series of small bolts/screws on the ends by the fender wells. The center is held in place by plastic pegs that you can get to from underneath the vehicle.

Step 2: Remove factory chrome bumper. TOW HOOK MODELS: You will need to remove tow hooks in order to mount frontier Lower frame bracket. Remount tow hook at same time you bolt up the lower frame Brackets. NON-TOW HOOK MODELS: Use ½" X 1 ¾" bolts supplied to mount Frontier lower frame brackets. In order to secure bracket as tight as possible you must install our ½" bolt through the pre-punched hole on top of the bracket and squeeze bracket tightly to the tip of frame using the steel plate provided as a washer.

**Step 3:** Place upper plastic bumper pad back in place **Step 4:** Install factory fog lights to front end using the 3/8" washers to hold light to steel bracket. Install Frontier FBR to lower frame brackets. Align + tighten all 4 bolts.

<u>Step 5:</u> Install Upper frame brackets to top of frame cap using the factory bolt.

**Step 6:** Check alignment of FBR to truck before tightening bolts on the upper brackets.

Bolt Bag Contents:	
Qty	Description
28	1/2" Flat Washers
14	1/2" Lock Washers
14	1/2" Hex Nuts
14	1/2" X 1 3/4" Bolts
2	Lower Frame Brkts
2	Upper Frame Brkts
6	3/8" flat washers
2	1/4" X 1" Bolts
2	1/4" Lock Washers
2	1/4" Hex Nuts
4	1/4" flat washers
2	Steel plate washers
4	Grommets/plugs
96	Total Pieces